

BROCK LATCH-LOCK® WALK-THROUGH DOOR SPECIFICATIONS

DOOR DESCRIPTION*†	DOOR OPENING DIMENSIONS		BIN DIAMETER	
	INCHES	MM	FEET	METERS
Latch-Bar Door #1	26 x 61.5	660 x 1562	15 to 30	4.6 to 9.1
Latch-Bar Door #2	26 x 61.5	660 x 1562	24 to 48	7.3 to 14.6
Latch-Bar Door #3	26 x 61.5	660 x 1562	27 to 54	8.2 to 16.5
Heavy Latch-Bar Doors #5 and #6	26 x 54	660 x 1372	30 to 90	9.1 to 27.4
Heavy Latch-Bar Doors #7, #8 and #9	26 x 50	660 x 1270	90 to 156	27.4 to 47.5

* Latch-Bar Doors #1 through #3 are not available for use in a bin with three inside stiffeners per sheet.

† Door type required is determined by bin model.

NOTE: A walk-through LATCH-LOCK® Door is standard on all BROCK® flat-bottom bins. A one-ring (tier) LATCH-LOCK Door is standard on BROCK® Commercial hopper-bottom bins and is available for all BROCK® flat-bottom grain bins.



— BROCK SOLID® —

BROCK GRAIN SYSTEMS

A Division of CTB, Inc.

A Berkshire Hathaway Company

Phone: +1 866.658.4191

www.brockgrain.com

Email: sales@brockgrain.com