


Brock Conveyor Capacities

Belt Speed (Feet per minute / Meters per second)

MODEL	UNITS	400/2.0	450/2.3	500/2.5	550/2.8	600/3.0	650/3.3	700/3.6
26	Bu/Hr MT/Hr	10300 261	11600 294	12900 327	14100 359	16400 392	16700 425	18000 457
30	Bu/Hr MT/Hr	13100 333	14800 376	16400 417	18100 459	19700 501	21400 542	23000 584
36	Bu/Hr MT/Hr	17100 435	19300 490	21400 544	23600 599	25700 653	27900 708	30000 762
42	Bu/Hr MT/Hr	22900 581	25700 653	28600 726	31400 798	34300 871	37100 943	40000 1016
48	Bu/Hr MT/Hr	27600 701	31100 789	34500 876	38000 964	41400 1052	44900 1139	48300 1227
54	Bu/Hr MT/Hr	33000 838	37200 944	41300 1049	45400 1154	49600 1259	53700 1364	57800 1468

Conveyor Dimensions

Belt Width		"A"		"B"		"C"	
INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
26	650	33	838	32	813	29.3	744
30	750	37	940	36	914	29.6	752
36	900	43	1092	42	1067	30.2	767
42	1050	49	1245	48	1220	30.8	782
48	1200	55	1397	54	1372	31.1	790
54	1350	61	1549	60	1524	32.0	813



— BROCK SOLID® —

Safeguarding Your Grain® Since 1957

BROCK GRAIN SYSTEMS

A Division of CTB, Inc.

A Berkshire Hathaway Company

Phone: +1 866.658.4191

www.brockgrain.com

Email: sales@brockgrain.com