

MEYER ENERGY MISER® Tower Dryer Specifications

Dryer Model		1000S	1200S	1400S	1600S	1800S	2000S	2400S	2650S
Dryer Diameter	Feet/Inches	11' 8"	11' 8"	11' 8"	11' 8"	11' 8"	11' 8"	11' 8"	11' 8"
	Meters	3.56	3.56	3.56	3.56	3.56	3.56	3.56	3.56
Overall Height	Feet/Inches	42' 10"	47' 10"	54' 1"	57' 10"	61' 7"	66' 7"	75' 4"	81' 7"
	Meters	13.06	14.58	16.48	17.63	18.77	20.29	22.96	24.87
Grain Column Width	Inches	12 & 10	12 & 10	12 & 10	12 & 10	12 & 10	12 & 10	12 & 10	12 & 10
	Millimeters	305 & 254	305 & 254	305 & 254	305 & 254	305 & 254	305 & 254	305 & 254	305 & 254
Double-Wide Double-Inlet Blower (Quantity - horsepower)		2 - 30	2 - 30	2 - 30	2 - 40	2 - 40	2 - 50	2 - 50	2 - 60
Typical burner use at 60°F./15.6° C. Suction Cool (Million BTU / hr)		5.8	6.4	6.7	8.6	8.8	9.6	10.8	11.4
Typical burner use at 10°F./-12.2° C. Suction Cool (Million BTU / hr)		7.5	8.2	8.6	11.0	11.2	12.2	13.8	14.5
Unloading Motor (Horsepower)		5	5	5	5	5	5	5	5

Grain Dryer Capacities*

Dryer Model		1000S	1200S	1400S	1600S	1800S	2000S	2400S	2650S
Corn Dry/Cool 20% to 15%	Bushels per Hour	1,000	1,200	1,400	1,600	1,800	2,000	2,400	2,650
	Metric Tons per Hour	25	30	36	41	46	51	61	67
Corn Dry/Cool 25% to 15%	Bushels per Hour	600	720	840	960	1,080	1,200	1,440	1,590
	Metric Tons per Hour	15	18	21	24	27	30	37	40
Corn Full Heat 20% to 15%**	Bushels per Hour	1,670	1,860	2,070	2,380	2,520	2,730	3,030	3,315
	Metric Tons per Hour	42	47	53	60	64	69	77	84
Corn Full Heat 25% to 15%**	Bushels per Hour	990	1,110	1,230	1,410	1,500	1,620	1,820	1,980
	Metric Tons per Hour	25	28	31	36	38	41	46	50

*Drying capacities are the result of a combination of field tests and averages of customer-reported capacities. These capacities should be attainable in one pass with mature, unfrozen, clean (maximum of 2% fines) grain when operating the dryer at the recommended drying temperature. Drying capacities will vary depending upon weather conditions, hybrid variety, grain maturity, and cleanliness of the grain.

**Final moisture in bin after steeping and cooling. Final moisture in bin can be affected by ambient conditions, steeping times and cooling rates.



—BROCK SOLID®—

Safeguarding Your Grain® Since 1957

BROCK GRAIN SYSTEMS

A Division of CTB, Inc.

A Berkshire Hathaway Company

Phone: +1 866.658.4191

www.brockgrain.com

Email: sales@brockgrain.com

BR-2060/202508